

Variostep Classic

Level to use according to EN 13329:

Klasa 23 / 32 - AC4

Domestic with heavy use

Commercial with general use



Product quality		
Dimension	thickness (d)	8,00 ± 0,50 mm dmax - dmin ≤ 0,50 mm
	length	1285 ± 0,50 mm dmax - dmin ≤ 0,50 mm
	width (b)	192,0 ± 0,10 mm bmax - bmin ≤ 0,20 mm
Structure		UW/GT/NL/RF/NO
Panels per box		9
Boxes per pallet		52
Tolerance		
Squareness	EN 13329	≤ 0,20 mm
Straightness	EN 13329	≤ 0,30 mm
Openings between elements	EN 13329	average: ≤ 0,15 mm max: ≤ 0,20 mm
Height difference between elements	EN 13329	average: ≤ 0,10 mm max: ≤ 0,15 mm
Test		
Impact test -small ball		EN 13329
Impact test -big ball		EN 13329
Stain resistance	Group 1 i 2	EN 13329
	Group 3	EN 13329
Sweeling after 24h		EN 13329
Surface soudness		EN 13329
Locking strenght		EN 13329
Abrasion resistance		EN 13329
Environment		
PCP conect		CEN/TR14823
Emission of Formaldehyd		EN 717-1
Physical characteristics		
Reaction to fire		EN 13501-1
Slip resistance		EN 13893

