

Product Information

Norm	EN ISO 26986	* check individual ref. for available widths			
Intensity of use	ISO 10874 (EN 685)		23 High domestic 32 Moderate commercial use 41 Light industrial use	class	
Total Thickness	EN ISO 24346 (EN 428)		2,90	mm	
Wearlayer	EN ISO 24340 (EN 429)		0,40	mm	
Abrasion group	EN 660-2		T	class	
Total weight	EN ISO 23997 (EN 430)		1950	g/m²	
Standard width	EN ISO 24341 (EN 426)		2 - 4 - 5 *	m	
Standard length	EN ISO 24341 (EN 426)		+/- 28	m	

Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%	
Curling	EN ISO 23999		≤ 8	mm	
Light stability	EN ISO 105 B02		≥ 6	degree	
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,20	mm	
Impact sound improvement	EN ISO 717/2		ΔLw 16	dB	
Dynamic coefficient of friction	EN 13893		> 0,6		
Slip resistance (ramp test with oil)	DIN 51130		R10	scale	
Reaction to fire Report number ---- VNLf 031380.4	EN 13501-1		Bfl-s1	class	
Underfloor heating	EN 12667		Suitable		
Thermal resistance	ISO 8302		0,025	m²K/w	
Thermal conductivity	EN 12524		0,12	W/m.K	
Chemical resistance	ISO 26987 (EN 423)		resistant		
Static Electrical Propensity	EN 1815		< 2kV	On concrete	

Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)



Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)



100% phthalate free
*for all products produced from May 2017 onwards

Product Build

1. PU lacquer
2. Wear layer
3. Design layer
4. Foam layer
5. Impregnation layer
6. Glass fibre interlayer
7. Backing



Features

